



CENTRIFUGAL PUMPS PRODUCT OVERVIEW

PROVEN TECHNOLOGY

DESMI

DESMI Centrifugal Pumps

DESMI is co-operating with the customers to develop innovations in pump technology. Whether it is solving individual application problems or developing new ideas, we are always looking for ways of doing things better.

DESMI's range of centrifugal pumps represents the latest developments, based on more than 150 years of experience in the pump industry.

The pumps are characterised by high-level efficiency and low NPSH values.

DESMI vertical pumps require minimal space and provide easy access for maintenance of the pump's rotating parts.



DESMI ESL



DESMI ESLH



DESMI ESLHT

Single-stage, End-suction

ESL/ESLH In-line and end-suction single-stage centrifugal pump	
Nominal diameter (DN)	25 to 100
Flow rate - 50Hz	Up to 200 m ³ /h (880 US gpm)
Flow rate - 60 Hz	Up to 250 m ³ /h (1100 US gpm)
Head	Up to 65 m (210 ft)
Pressure	Up to 30 bar (435 psi)
Temperature	Up to 140°C (284°F)
Motor	Standard and EX motors
VFD	Direct or wall-mounted
Applications: Water, water with additives, seawater and oils up to 500 cSt.	

Horizontal, End-suction

ESLHT Horizontal end-suction centrifugal Pump	
Norminal Diameter (DN)	25 to 65
Flow rate - 50 Hz	Up to 100 m ³ /h (440 US gpm)
Flow rate - 60 Hz	Up to 120 m ³ /h (530 US gpm)
Head	Up to 65m (220 ft)
Pressure	Up to 30 bar (435 psi)
Temperature	Up to 180°C (356 °F)
Motor	Standard and Ex motor
VFD	Direct or Bulkead/Wall-mounted
Applications: High temperatures water circulation, boiler water circulation, hot water supply or other heat transfer applications.	



DESMI NSL Horizontal



DESMI NSL



DESMI NSLH



DESMI NSLV

In-line, Vertical & Horizontal

NSL Vertical and horizontal in-line centrifugal pump	
Norminal Diameter (DN)	80 to 350
Flow rate - 50 Hz	Up to 2000 m ³ /h (8800 US gpm)
Flow rate - 60 Hz	Up to 2400 m ³ /h (10600 US gpm)
Head	Up to 195 m (640 ft)
Pressure	Up to 25 bar (360 psi)
Temperature	Up to 140°C (284 °F)
Motor	Standard and Ex motor
VFD	Direct or Bulkead/Wall-mounted
ATEX approved	
Applications: Water, water with additives, seawater and oils up to 500 cSt.	

End-suction

NSLH/V Vertical and horizontal end-suction centrifugal pump	
Nominal diameter (DN)	80 to 400
Flow rate	Up to 1800 m ³ /h (7900 US gpm)
Head	Up to 220 m (720 ft)
Pressure	Up to 25 bar (363 psi)
Temperature	Up to 150°C (302°F)
Motor	Standard and EX motors
VFD	Direct or wall-mounted
ATEX approved.	
Applications: Water, water with additives, seawater and oils up to 500 cSt.	

DESMI Centrifugal Pumps



DESMI DSL



DESMI DSL Horizontal



DESMI Modular S



DESMI Modular S Monobloc

Double Suction, In-line

DSL Vertical and horizontal inline double suction centrifugal pump	
Nominal diameter (DN)	150 to 600
Flow rate - 50 Hz	Up to 6200 m ³ /h (27300 US gpm)
Flow rate - 60 Hz	Up to 7400 m ³ /h (32580 US gpm)
Head	Up to 140 m (459 ft.)
Pressure	Up to 25 bar (363 psi)
Temperature	Up to 140°C (284°F)
Motor	Standard and Ex motors
VFD	Wall-mounted
ATEX approved.	
Applications: Water with additives and seawater.	

Self-priming

Modular S Self-priming centrifugal pump	
Norminal Diameter (DN)	32 - 125
Flow rate - 50 Hz	Up to 340 m ³ /h (1500 US gpm)
Flow rate - 60 Hz	Up to 410 m ³ /h (1800 US gpm)
Head	Up to 140 m (460 ft)
Pressure	Up to 16 bar (230 psi)
Temperature	Up to 140°C (284 °F)
Motor	Standard and Ex motor
VFD	Direct or Bulkead/Wall-mounted
ATEX approved	
Applications: Water, water with additives, seawater and oils up to 500 cSt.	



DESMI SA

Self-priming

SA / SAEN Horizontal self-priming centrifugal pump	
Norminal Diameter (DN)	20 to 200
Flow rate - 50 Hz	Up to 610 m ³ /h (2700 US gpm)
Flow rate - 60 Hz	Up to 730 m ³ /h (3200 US gpm)
Head	Up to 115 m (375 ft)
Pressure	Up to 12 bar (170 psi)
Temperature	Up to 140°C (284 °F)
Motor	Standard and Ex motor
VFD	Direct or Bulkead/Wall-mounted
Applications: Water, water with additives, seawater and oils up to 500 cSt.	

DESMI High Flow - Low Pressure Pumps



DESMI NSLV

Vertical, End-suction



DESMI NSLH

Horizontal, End-suction

NSLV Vertical End-suction Pump - High Flow - Low Pressure	
Nominal diameter	DN 250 to 600
Flow rate	500 to 6400 m ³ /h (2201 to 28.178 US GPM)
Head	2 mLC - 20 mLC
Pressure	5 bar (PN5) (72.5 psi)
Temperature	0 to 100 °C (212 °F)
Motor	Standard and Ex motors
Motor size	From 7.5 kW to 200 kW
VFD	Fully compatible
Materials	Cast Iron (GG20) (with or without Ceramic Coating for seawater), Stainless Steel (AISI316 & 1.4410), NiAlBz

NSLH Horizontal End-Suction Centrifugal Pump	
Nominal diameter	DN 250 to 600
Flow rate	500 to 6400 m ³ /h (2201 to 28.178 US GPM)
Head	2 mLC - 20 mLC
Pressure	5 bar (PN5) (72 psi)
Temperature	0 to 100 °C (212 °F)
Motor	Standard and Ex motors
Motor size	From 7.5 kW to 250 kW
VFD	Fully compatible
Materials	Cast Iron (GG20) (with or without Ceramic Coating for seawater), Stainless Steel (AISI316 & 1.4410), NiAlBz

DESMI Vertical Centrifugal Multi-stage Pumps

Multi-stage

Vertical DPV	
2-pole	2, 4, 6, 10, 15, 25, 40, 60, 85, 125
4-pole	15, 25, 40, 60, 85, 125
Capacity range (m ³ /h)/(gpm)	0.5-193/2-849
Maximum pump pressure (m)/(ft)	5/16 to 400/1312
Temperature range medium	-20 - +140° C / -4 - 284° F
Applications: Water, sprinkler, industry, cleaning systems and boiler feeds.	




DESMI DPV Pumps


DESMI Centrifugal Pumps - DSL 50Hz




DSL Centrifugal Pump, 960 rpm, **50 HZ**



DSL Centrifugal Pump, 1450 rpm, **50 HZ**



DSL Centrifugal Pump, 1152 rpm, 60 Hz




Capacity: 1 m³/H = 4.4 USGPM

TOTAL HEAD: 1 M = 3.28 FEET

• MAX EFFICIENCY

DSL Centrifugal Pump, 1740 rpm, 60 Hz




Capacity: 1 m³/H = 4.4 USGPM

TOTAL HEAD: 1 M = 3.28 FEET


• MAX EFFICIENCY



ESL Centrifugal Pump, 960 rpm, **50 HZ**




ESL Centrifugal Pump, 1450 rpm, **50 HZ**



DESMI Centrifugal Pumps - ESL


ESL Centrifugal Pump, 2950 rpm, **50 HZ**



DESMI Centrifugal Pumps - ESLHT




ESLTH Centrifugal Pump, 2950 rpm, **50 HZ**




DESMI Centrifugal Pumps - ESL 60Hz



ESL Centrifugal Pump, 1152 rpm, **60 Hz**




ESL Centrifugal Pump, 1740 rpm, **60 Hz**



DESMI Centrifugal Pumps - ESL


ESL Centrifugal Pump, 3450 rpm, **60 HZ**



DESMI Centrifugal Pumps - ESLHT




ESLTH Centrifugal Pump, 3450 rpm, **60 HZ**



DESMI Centrifugal Pumps - Modular S 50Hz




S Centrifugal Pump, 960 rpm, **50 HZ**




DESMI Centrifugal Pumps - Modular S 50Hz

S Centrifugal Pump, 1450 rpm, **50 Hz**




S Centrifugal Pump, 2950 rpm, **50 Hz**




DESMI Centrifugal Pumps - Modular S 60Hz



S Centrifugal Pump, 1152 rpm, **60 HZ**




S Centrifugal Pump, 1740 rpm, **60 HZ**



DESMI Centrifugal Pumps - Modular S 60Hz


S Centrifugal Pump, 3450 rpm, **60 HZ**




DESMI Centrifugal Pumps - NSL 50Hz



NSL Centrifugal Pump, 960 rpm, **50 HZ**




NSL Centrifugal Pump, 1450 rpm, **50 HZ**



DESMI Centrifugal Pumps - NSL 50Hz


NSL Centrifugal Pump, 2950 rpm, **50 Hz**



DESMI Centrifugal Pumps - NSLV & NSLH 50Hz



NSLV/NSLH Centrifugal Pump, **50 Hz**




*The pump curve is obtained on variable speed control on full diameter impeller.
These model's maximum rotation speed are different from 1000 rpm to 1850 rpm*


DESMI Centrifugal Pumps - NSL 60Hz



NSL Centrifugal Pump, 1152 rpm, **60 HZ**




NSL Centrifugal Pump, 1740 rpm, **60 HZ**



DESMI Centrifugal Pumps - NSL 60Hz


NSL Centrifugal Pump, 3450 rpm, **60 HZ**



DESMI Centrifugal Pumps - NSLV & NSLH 60Hz




NSLV/NSLH Centrifugal Pump, **60 HZ**




The pump curve is obtained on variable speed control on full diameter impeller.
 These model's maximum rotation speed are different from 1000 rpm to 1850 rpm

DESMI Centrifugal Pumps - SA 50Hz




SA Centrifugal Pump, 960 rpm, **50 HZ**




DESMI Centrifugal Pumps - SA 50Hz

SA Centrifugal Pump, 1450 rpm, **50 Hz**




SA Centrifugal Pump, 2950 rpm, **50 Hz**




DESMI Centrifugal Pumps - SA 60Hz

SA Centrifugal Pump, 1152 rpm, **60 HZ**





SA Centrifugal Pump, 1740 rpm, **60 HZ**



DESMI Centrifugal Pumps - SA 60Hz

SA Centrifugal Pump, 3450 rpm, **60 Hz**





ROTAN® GP



ROTAN® HD



ROTAN® PD



ROTAN® CD



ROTAN® ED



ROTAN® HD 202

Internal Gear Pumps

	ROTAN® GP - General Purpose	ROTAN® HD - Heavy Duty	ROTAN® PD - Petrochemical Duty	ROTAN® CD - Chemical Duty	ROTAN® ED - Environmental Duty
Capacity range	Up to 50 m ³ /h / 220 gpm	Up to 250 m ³ /h / 1100 gpm	Up to 250 m ³ /h / 1100 gpm	Up to 250 m ³ /h / 1100 gpm	Up to 90 m ³ /h / 396 gpm
Speed	Up to 1750 rpm	Up to 1750 rpm	Up to 1750 rpm	Up to 1750 rpm	Up to 1750 rpm
Differential pressure	Up to 16 bar / 232 psi	Up to 16 bar / 232 psi	Up to 16 bar / 232 psi	Up to 16 bar / 232 psi	Up to 16 bar / 232 psi
Suction lift	Up to 0.5 / 7.25 psi bar vacuum while priming Up to 0.8 bar / 11.6 psi vacuum while pumping	Up to 0.5 bar / 7.25 psi vacuum while priming Up to 0.8 bar / 11.6 psi vacuum while pumping	Up to 0.5 bar / 7.25 psi vacuum while priming Up to 0.8 bar / 11.6 psi vacuum while pumping	Up to 0.5 bar / 7.25 psi vacuum while priming Up to 0.8 bar / 11.6 psi vacuum while pumping	Up to 0.5 bar / 7.25 psi vacuum while priming Up to 0.8 bar / 11.6 psi vacuum while pumping
Viscosity range	Up to 7,500 cSt	Up to 250,000 cSt	Up to 250,000 cSt	Up to 250,000 cSt	Up to 10,000 cSt
Temperature	Up to 150°C / 302°F	Up to 250°C / 482°F	Up to 250°C / 482°F	Up to 250°C / 482°F	Up to 250°C / 482°F
Pump medium:	Clean oil, glycol, vegetable oil, solvents, lube oil, waste oil, fish oil, also for marine fuel, diesel, gas, and lube oil.	Oil, asphalt, chocolate, paint/lacquer, molasses, soap, additive, polyol, viscose, sulphate soap, maltose, grease, pitch, base oil, bitumen, polyester, also for marine fuel, diesel, gas, and lube oil.	Fuel, oil, gasoline, lube oil, grease, other hydrocarbon based fluids, additives, bitumen, polystyrene, wax	Organic acid, fatty acid, alkali, caustic soda, polymer solutions, soap, shampoo, animal fat, vegetable fat, chocolate, other special fluids, resin, paint, rosin	Isocyanate, solvents hazardous organic liquids, printing ink, resin, pitch, alkyd resin, soyabean oil, linseed oil, monomers, polyol, corn syrup, also for marine fuel, diesel, gas, and lube oil.



AFTER SALES & SERVICE

DESMI always strives to provide our customers with the very best service! That's why we have established DESMI DeServe - your guarantee for an excellent service 24/7/365.

24-hour hotline: +45 96 32 81 10

Service: service@desmi.com

Spare Parts: spareparts@desmi.com



DESMI Genuine Spare Parts Kits for Simple Overhaul and Service

DESMI provides spare parts kits for easy and simple maintenance and overhaul of your pumps. We offer a variety of spare parts kits for a number of DESMI pump series.

To determine which spare parts kit you need and to provide you with the best service, we need to have the following information:

- Pump type (e.g. NSL 150-265)
- Serial number (e.g. 323249 or 30192-1)

Spare Parts Kits include:


- Mechanical shaft seal
- Special tool
- Bearings
- O-rings
- Gaskets
- Washers & nuts
- Item list
- Etc.



Overhaul videos at www.desmi.com/overhaul.aspx



Parts numbers and flyers at www.desmi.com/parts.aspx



Manuals at www.desmi.com/aftersales

THE DESMI GROUP - ONE GLOBAL COMPANY

DESMI offices:

Africa

DESMI Africa Ltd.
Tel.: +255 222 600014

Canada

DESMI Inc.
Tel.: +1 905 321 3471

China

DESMI Pumping Technology (Suzhou) Co., Ltd.
Tel.: +86 512 6274 0400

DESMI Pumping Technology (Suzhou) Co., Ltd.
Shanghai Liaison Office
Tel.: +86 21 6071 06 00-05, 6071 06 07-13

DESMI Pumping Technology (Suzhou) Co., Ltd.
Tianjin Liaison Office
Tel.: +86 22 2317 0467

DESMI Pumping Technology (Suzhou) Co., Ltd.
Guangzhou Liaison Office
Tel.: +86 20 2831 3973

DESMI Pumping Technology (Suzhou) Co., Ltd.
Chongqing Liaison Office
Tel.: +86 23 8823 3518

DESMI Pumping Technology (Xuancheng)
Co., Ltd.
Tel.: +86 563 2612 570

Denmark

DESMI A/S - Group Head Quarter
Tagholm 1
DK-9400 Nørresundby
Tel.: +45 96 32 81 11

DESMI Pumping Technology A/S
Tel.: +45 96 32 81 11

DESMI Danmark A/S
Tel.: +45 72 44 02 50

DESMI Ro-Clean A/S
Tel.: +45 65 48 16 10

DESMI Ocean Guard A/S
Tel.: +45 96 32 81 99

France

DESMI SARL
Tel.: +33 130 439 710

Germany

DESMI GmbH
Tel.: +49 407 519847

Greece

DESMI Pumping Technology A/S Greek Branch
Tel.: +30 2114 111 893

India

DESMI India LLP
Toll Free Number: 1800 123 123 001

Indonesia

DESMI Ro-Clean APAC
Tel.: +62 21 23585636

Korea

DESMI Korea
Tel.: +82 51 723 8801

Netherlands

DESMI B.V.
Tel.: +31 30 261 00 24

Norway

DESMI Norge AS
Tel.: +47 38 12 21 80

Poland

DESMI Sp. z o.o.
Tel.: +48 22 676 91 16

Singapore

DESMI Singapore Pte Ltd.
Tel.: +65 62 50 71 77

Sweden

DESMI Sweden
Tel.: +46 31 304 51 30

UAE

DESMI Pumping Technology A/S (Br.)
Dubai Office
Tel.: +971 4 320 0499

Abu Dhabi Office
Tel.: +971 50-821 4979

U.K.

DESMI Ltd.
Tel.: +44 1782 566900

DESMI FHS Ltd.
Tel.: +44 1782 566900

USA

DESMI Inc.
Tel.: +1 757 857 7041

- DESMI Companies
- DESMI Dealers/Agents

Need more information or specifications? Contact us at desmi@desmi.com or read more about DESMI and DESMI's other products and solutions at www.desmi.com

MARINE & OFFSHORE

INDUSTRY

ENVIRO-CLEAN

DEFENCE & FUEL

UTILITY