

RO-SKIM

- An Integrated Boom and Skimming System

The RO-SKIM is a special section of RO-BOOM that has been fitted with a weir and DESMI DOP 250 or DOP 160 pump.

The RO-SKIM is available in five sizes to mate with RO-BOOM 1000, 1300, 1500, 1800 and 2000.

The weir is ideally placed for collection of the oil that is building up against the face of the RO-BOOM.

One or two RO-SKIM units can be coupled together in one long boom assembly offering a high recovery rate.

The RO-SKIM is ideal for open sea sweeping operations.



The RO-SKIM is positioned at the optimum location for oil recovery.

RO-SKIM



Advantages of RO-SKIM:

- Modular system that allows configurations to be built according to requirements.
- RO-SKIM is a special section of RO-BOOM – independent skimmer and boom configurations.
- Weir built into the boom system and therefore follows the wave movements.
- Skimming depth can be remotely adjusted.

TECHNICAL DATA

	RO-SKIM 2000,1800,1500	RO-SKIM 1300 & 1000
Standard length:	1.0 m	1.0 m
Nameplate capacity:	100 to 125 m ³ per hour	30 m ³ per hour
Max discharge pressure:	10 bar	10 bar
Freeboard	2000 – 0,59 1800 – 0,59 1500 – 0,52	1300 – 0,45 1000 – 0,38
Draft	2000 – 1,10 1800 – 0,90 1500 – 0,72	1300 – 0,63 1000 – 0,43
Onboard pump:	DESMI DOP-250	DESMI DOP-160
Weight with pump:	125-150 kg	60-85 kg
Inlet weir:	Hydraulic remotely adjusted	Hydraulic remotely adjusted
Pump discharge:	4, 5 or 6 inch Camlock	3 inch Camlock
Max hydraulic demand:	160 liters 210 bar	80 liters 210 bar

RO-SKIM

Hose sets and hydraulic power units are available for the operation of one or multiple RO-SKIMs.

- Contact one of the offices below for further information



All information is subject to change, and pictures are for illustration purposes only, and not necessarily correct.

www.desmiro-clean.com



Head Office
 DESMI Ro-Clean A/S
 Hestehaven 61
 DK-5260 Odense S
 Phone: +45 65 48 16 10
 Fax: +45 65 48 16 15
 E-mail: Denmark.desmiro-clean@desmi.com

U.S.A. Office
U.K. Office
Latin America Office
Asia Office
China Office
Korea Office
Norway Office

APPLIED FABRIC TECHNOLOGIES INC, Tel.: +1 716 662 0632, E-mail: bestboom@afti.com
DESMI Ro-Clean Ltd, Tel. +44 23 80829751, E-mail: uk.desmiro-clean@desmi.com
DESMI Ro-Clean Latioanoamerica S.A., Tel.: +593 2 326 1939, E-mail: Latinoamerica.desmiro-clean@desmi.com
DESMI Ro-Clean Asia, Tel: +62 21 2358 4468, E-mail: asia.desmiro-clean@desmi.com
 DESMI Ro-Clean, DESMI Pumping Technology (Suzhou) Co., Ltd., Tel.: +86 512 6274 0400, E-mail: China.desmiro-clean@desmi.com
DESMI Ro-Clean, DESMI Korea, Gyeonggi, Tel.: +82 31 931 5701, E-mail: Korea.desmiro-clean@desmi.com
DESMI Ro-Clean, DESMI Norge AS, Kristiansand S, Tel.: +47 3812 2180, E-mail: Norway.desmiro-clean@desmi.com