



DESMI
Make life flow

Marine & Offshore

Pump Solutions

Marine

DESMI
Make life flow

DESMI Centrifugal Pumps

DESMI centrifugal pumps are used as cooling, ballast, fire, and bilge pumps for fresh as well as seawater. The pumps are available with capacities up to 7400 m³/h/32600 US gpm and delivery heads up to 200 mWC.

Our product range is based on the modular principle which gives interchangeability of the most commonly used items and consequently a quick and safe supply of spare parts.

DESMI pumps are also installed in many naval vessels where special requirements as to materials, shock resistance etc. apply.

Single pumps or complete packages, DESMI's staff will always find the correct solution. Our world-wide network of subsidiaries and distributors ensures prompt spare parts supply and first-class after-sales-service.

DESMI Centrifugal Pumps (Vertical Pumps)

DSL

Vertical In-line Double Suction / Centrifugal Pump DSL	
Norminal Diameter (DN)	150 to 600
Flow rate - 50 Hz	Up to 6200 m ³ /h (27300 US gpm)
Flow rate - 60 Hz	Up to 7400 m ³ /h (32600 US gpm)
Head	Up to 140 m (460 ft)
Pressure	Up to 25 bar (360 psi)
Temperature	Up to 140°C (284 °F)
Motor	Standard and Ex motor
VFD	Bulkhead/Wall-mounted
ATEX approved.	

Applications: Ballast and cooling water pumping are among the many tasks that the DSL pumps solve to perfection. But also district heating and power plants together with many other industries will profit from using DSL pumps. Pump materials available in bronze, cast iron and stainless steel.

NSL

Vertical In-line Single Suction / Centrifugal Pump NSL	
Norminal Diameter (DN)	80 to 350
Flow rate - 50 Hz	Up to 2000 m ³ /h (8800 US gpm)
Flow rate - 60 Hz	Up to 2400 m ³ /h (10600 US gpm)
Head	Up to 195 m (640 ft)
Pressure	Up to 25 bar (360 psi)
Temperature	Up to 140°C (284 °F)
Motor	Standard and Ex motor
VFD	Direct or Bulkead/Wall-mounted
ATEX approved	

Applications: Various marine applications such as seawater cooling systems, LT-cooling systems, HT-cooling systems, ballast water pumps and fire pumps. Pump materials available in bronze, cast iron and stainless steel.

NSLV / NSLH

Vertical and Horizontal end-suction / Centrifugal Pump NSLV / NSLH	
Norminal Diameter (DN)	65 to 600
Flow rate - 50 Hz	Up to 6200m ³ /h (27300 US gpm)
Flow rate - 60 Hz	Up to 5900m ³ /h (26000 US gpm)
Head	Up to 200 m (660 ft)
Pressure	Up to 25 bar (360 psi)
Temperature	Up to 140°C (284 °F)
Motor	Standard and Ex motor
VFD	Direct or Bulkead/Wall-mounted
ATEX approved	

The DESMI NSLV pumps are constructed for vertical mount (with suction flange downwards) and the NSLH pump for horizontal mounting.

Applications: The pumps are particularly suitable for the pumping of water in connection with cooling systems, cooling of diesel engines, as bilge pumps, ballast pumps, fire pumps, brine pumps, pumps for irrigation, fish farms, water works, district heating, salvage corps, army and navy, etc.

DSL Benefits:

- Suction design provides a perfect flow
- High efficiency and low NPSH values



DSL



NSL

NSL Benefits:

- High efficiency
- Low NPSH values
- Easy installation/service
- Various materials

- High efficiency
- Low NPSH values
- Easy installation/service
- Various materials and further, an attractive price.



NSLV



NSLH

DESMI Centrifugal Pumps (Vertical Pumps and horizontal)

ESL/ESLH

Vertical In-line / Horizontal end-suction Centrifugal Pump ESL / ESLH	
Norminal Diameter (DN)	25 to 100
Flow rate - 50 Hz	Up to 200 m ³ /h (880 US gpm)
Flow rate - 60 Hz	Up to 250 m ³ /h (1100 US gpm)
Head	Up to 65 m (220 ft)
Pressure	Up to 30 bar (435 psi)
Temperature	Up to 140°C (284 °F)
Motor	Standard and Ex motor
VFD	Direct or Bulkead/Wall-mounted
ATEX approved	

Applications: Various water applications such as hot water circulation, fresh water circulation, refrigeration, HVAC, hydrophore pump, cooling water. Pump materials available in bronze, cast iron and stainless steel.

ESL Benefits:

- High efficiency
- Low NPSH values
- Compact design
- Easy installation
- Low maintenance costs




Magdrive Pump

Vertical In-line Single Suction / Centrifugal Pump NSL	
Norminal Diameter (DN)	25 to 100
Flow rate - 50 Hz	Up to 150 m ³ /h (660 US gpm)
Flow rate - 60 Hz	Up to 180 m ³ /h (800 US gpm)
Head	Up to 130 m (430 ft)
Pressure	Up to 16 bar
Temperature	Min. -40°C / Max. 120°C
Motor	Standard and Ex motor
Viscosity Range	Min. 0.3 / Max. 300 cSt
ATEX approved	
Common Applications: Where no pumping medium leakage is allowed	

Pumping of: Methanol, Ethanol, Hydrocarbons (fuels), Ammonia & Amine/Water Mixtures.
Note:
 The pumps are designed for pumping liquids without solid/clogging particles. These could cause premature failure of the pump bearings and/or mag-drive.

Benefits:

- Efficient
- Reliable
- Cost-effective



DESMI Centrifugal Pumps (Vertical Pumps and horizontal)

ESLHT

Horizontal end-suction / Centrifugal Pump ESLHT	
Norminal Diameter (DN)	25 to 65
Flow rate - 50 Hz	Up to 100 m ³ /h (440 US gpm)
Flow rate - 60 Hz	Up to 120 m ³ /h (530 US gpm)
Head	Up to 65m (220 ft)
Pressure	Up to 30 bar (435 psi)
Temperature	Up to 180°C (356 °F)
Motor	Standard and Ex motor
VFD	Direct or Bulkead/Wall-mounted

Applications: High temperatures water circulation e.g., marine boiler water circulation, hot water supply or other heat transfer applications.

ESLHT Benefits:

- High efficiency
- Compact design
- High temperature liquid transportation and circulation



TSL & TSLH

Vertical in-line / Horizontal Two-stage Centrifugal Pump TSL & TSLH	
Norminal Diameter (DN)	40 & 50
Flow rate - 50 Hz	Up to 40 m ³ /h (180 US gpm)
Flow rate - 60 Hz	Up to 48 m ³ /h (210 US gpm)
Head	Up to 135 m (440 ft)
Pressure	Up to 16 bar (230 psi)
Temperature	Up to 140°C (284 °F)
Motor	Standard and Ex motor
VFD	Direct or Bulkead/Wall-mounted

Applications: Boiler water supply, Ballast water backflush, Sprinkler, Fire water jockey, EGCS demist cleaning, Industrial cleaning, Water treatment and filtration

TSL Benefits:

- Two-stage, single-suction
- Vertical or horizontal
- High differential pressure
- Flow up to 48 m³/h



DESMI Centrifugal Pumps (Horizontal Pumps)

A DESMI speciality is horizontal, self-priming pumps where suction is based on the diffuser principle and the pump itself is able to

evacuate the suction line at suction lifts up to 8.5 m / 278 ft.

Modular S

Horizontal Self-priming / Centrifugal Pump Modular S	
Norminal Diameter (DN)	32 - 125
Flow rate - 50 Hz	Up to 340 m ³ /h (1500 US gpm)
Flow rate - 60 Hz	Up to 410 m ³ /h (1800 US gpm)
Head	Up to 140 m (460 ft)
Pressure	Up to 16 bar (230 psi)
Temperature	Up to 140°C (284 °F)
Motor	Standard and Ex motor
VFD	Direct or Bulkead/Wall-mounted
ATEX approved	

Applications: Bilge pumps, ballast pumps, fire pump, cooling-water pumps, deck-wash pumps and general service pumps.



SA

Horizontal self-priming Centrifugal pump SA / SAEN	
Norminal Diameter (DN)	20 to 200
Flow rate - 50 Hz	Up to 610 m ³ /h (2700 US gpm)
Flow rate - 60 Hz	Up to 730 m ³ /h (3200 US gpm)
Head	Up to 115 m (375 ft)
Pressure	Up to 12 bar (170 psi)
Temperature	Up to 140°C (284 °F)
Motor	Standard and Ex motor
VFD	Direct or Bulkead/Wall-mounted

Applications: Bilge pumps, ballast pumps, fire pumps, cooling water pumps, deck-wash pumps, fuel pumps, wellpoint pumps, irrigation pumps, circulation pumps.



Close Coupled Self-priming Centrifugal Pump

NSA

Close coupled self-priming / Centrifugal pump NSA	
Norminal Diameter (DN)	50 to 80
Flow rate - 50 Hz	Up to 70 m ³ /h (300 US gpm)
Head	Up to 50 m (160 ft)
Pressure	Up to 12 bar (170 psi)
Temperature	Up to 140°C (284 °F)
Motor	Standard and Ex motor
VFD	Direct or Bulkead/Wall-mounted

Applications: Bilge pumps, ballast pumps, general service pumps, emergency fire pumps, cooling water pumps



Dirty Water Vacuum Pump

VAC

Horizontal Self-priming / Centrifugal pump VAC	
Norminal Diameter (DN)	65 & 100
Flow rate - 50 Hz	Up to 70m ³ /h (300 US gpm)
Flow rate - 60 Hz	Up to 70m ³ /h (300 US gpm)
Head	Up to 19 m (60 ft)
Pressure	Up to 3.5 bar (50 psi)
Temperature	Up to 80°C (176 °F)
Motor	Standard and Ex motor
VFD	Direct or Bulkead/Wall-mounted

Applications: (Emergency) bilge pumps, bilge-ballast pumps, general service pumps, vacuum pumps, gland-leaking water pumps, chemical industries, draining holds, emptying vessels, well point systems



Priming Pump and Ejector

The DESMI Priming ejector / pump is designed for mounting on non-selfpriming centrifugal pumps making the pump unit self-priming.

Max. water flow pumped to drain after completed priming :	Approx. 25 liter/min for 50 Hz / approx. 33 liter/min for 60 Hz power supply. Depending on vacuum level and rpm during priming the water temperature in the pump can rise up to approx. 70°C/158°F within 20 minutes.
Max. allowed water temperature in the pump is	80°C/176°F.



Priming Ejector
For compressed air



Priming Pump
Electrically Driven

DESLUBE Submerged Lubrication Oil Pump

The DESLUBE series is a submerged deep-well pump designed for main engine lube oil supply for large two-stroke engines.

DESLUBE

Vertical Deepwell multistage / Centrifugal pump DESLUBE	
Norminal Diameter (DN)	150 to 300
Flow rate - 50 Hz	Up to 880 m ³ /h (3900 US gpm)
Flow rate - 60 Hz	Up to 1050 m ³ /h (4600 US gpm)
Head	Up to 125 m (410 ft)
Pressure	Up to 20 bar (290 psi)
Temperature	Up to 80°C (176 °F)
Motor	Standard and Ex motor
VFD	Direct or Bulkead/Wall-mounted

Applications:
The DESLUBE series is a submerged deep well pump designed for main engine lubrication oil supply for especially large two-stroke engines.

Benefits:

- Low NPSH
- Low noise
- Low vibration
- Low maintenance costs
- High reliability
- High flexibility




DESLUBE

Design Details


Pumps With Ø 215 And Ø 265 Impeller

Suction and discharge flange dimensions are identical. The line through inlet and outlet is flush with the centre line of the shaft. The pumps are mounted with one impeller wear ring.




Pumps With Ø 330, Ø 415 and Ø525 Impeller

Dimension of the suction flange is one size larger than that of the discharge flange. The line through inlet and outlet is tangential offset in relation to the centre line of the shaft. The pumps have two impeller wear rings.




Monobloc With Bearing

The pump is for major capacities and heavy loads, especially recommended where the advantage of the spacer coupling is of no importance and where a small overall height is required.



The pump is equipped with a separate rear cover with a ball bearing and a separate motor bracket. Dismantling of the rotating pump parts is possible without removing the pump casing from the piping.



Spacer


The pump is for high capacities, heavy loads, and high pump speeds. As a special feature the pump is equipped with a spacer coupling which is a combined distance and flexible coupling. This makes it possible to remove the complete bearing housing with shaft, bearings, shaft seal, and impeller without dismantling or loosening the motor or piping.

For high capacities and the resulting larger and heavier electric motors we recommend this pump version because of the easy dismantling of the rotating pump parts in connection with inspection and repair. This special feature is often a requirement within the marine industry where installations must be easy to service.




DESMI Centrifugal Pumps - DSL 50Hz

DSL Centrifugal Pump, 960 rpm, **50 HZ**



Capacity: 1 m³/H = 4.4 USGPM TOTAL HEAD: 1 M = 3.28 FEET • MAX EFFICIENCY


DSL Centrifugal Pump, 1450 rpm, **50 HZ**




Capacity: 1 m³/H = 4.4 USGPM TOTAL HEAD: 1 M = 3.28 FEET • MAX EFFICIENCY

DESMI Centrifugal Pumps - DSL 60Hz

DSL Centrifugal Pump, 1152 rpm, **60 Hz**




DSL Centrifugal Pump, 1740 rpm, **60 Hz**






DESMI Centrifugal Pumps - ESL 50Hz

ESL Centrifugal Pump, 960 rpm, **50 Hz**




ESL Centrifugal Pump, 1450 rpm, **50 Hz**



DESMI Centrifugal Pumps - ESL


ESL Centrifugal Pump, 2950 rpm, **50 Hz**



DESMI Centrifugal Pumps - ESLHT




ESLTH Centrifugal Pump, 2950 rpm, **50 Hz**






DESMI Centrifugal Pumps - ESL 50Hz

ESL Centrifugal Pump, 1152 rpm, **60 Hz**




ESL Centrifugal Pump, 1740 rpm, **60 Hz**



DESMI Centrifugal Pumps - ESL


ESL Centrifugal Pump, 3450 rpm, 60 Hz




DESMI Centrifugal Pumps - ESLHT




ESLTH Centrifugal Pump, 3450 rpm, 60 Hz



DESMI Centrifugal Pumps - Modular S 50Hz




S Centrifugal Pump, 960 rpm, **50 Hz**




DESMI Centrifugal Pumps - Modular S 50Hz

S Centrifugal Pump, 1450 rpm, 50 Hz




S Centrifugal Pump, 2950 rpm, 50 Hz




DESMI Centrifugal Pumps - Modular S 60Hz

S Centrifugal Pump, 1152 rpm, **60 Hz**



Capacity: 1 m³/H = 4.4 USGPM TOTAL HEAD: 1 M = 3.28 FEET • MAX EFFICIENCY


S Centrifugal Pump, 1740 rpm, **60 Hz**



Capacity: 1 m³/H = 4.4 USGPM TOTAL HEAD: 1 M = 3.28 FEET • MAX EFFICIENCY

DESMI Centrifugal Pumps - Modular S 60Hz


S Centrifugal Pump, 3450 rpm, 60 Hz



DESMI Centrifugal Pumps - NSL 50Hz




NSL Centrifugal Pump, 960 rpm, 50 Hz




DESMI Centrifugal Pumps - NSL 50Hz

NSL Centrifugal Pump, 1450 rpm, **50 Hz**




NSL Centrifugal Pump, 2950 rpm, **50 Hz**




DESMI Centrifugal Pumps - NSL 60Hz

NSL Centrifugal Pump, 1152 rpm, **60 Hz**




NSL Centrifugal Pump, 1740 rpm, **60 Hz**




DESMI Centrifugal Pumps - NSL 60Hz


NSL Centrifugal Pump, 3450 rpm, **60 HZ**



DESMI Centrifugal Pumps - SA 50Hz




SA Centrifugal Pump, 960 rpm, **50 Hz**




DESMI Centrifugal Pumps - SA 50Hz

SA Centrifugal Pump, 1450 rpm, **50 Hz**




SA Centrifugal Pump, 2950 rpm, **50 Hz**




DESMI Centrifugal Pumps - SA 60Hz

SA Centrifugal Pump, 1152 rpm, 60 Hz




SA Centrifugal Pump, 1740 rpm, 60 Hz



DESMI Centrifugal Pumps - SA 60Hz


SA Centrifugal Pump, 3450 rpm, 60 Hz





DESMI Centrifugal Pumps - NSA 50Hz


NSA Centrifugal Pump, 50 Hz



DESMI Centrifugal Pumps - VAC 50 & 60Hz




VAC Centrifugal Pump, 50 & 60 Hz



DESMI Centrifugal Pumps - TSL 50 og 60 Hz




TSL Centrifugal Pump, 50 Hz



Capacity: 1 m³/H = 4.4 USGPM TOTAL HEAD: 1 M = 3.28 FEET • MAX EFFICIENCY

TSL Centrifugal Pump, 60 Hz



Capacity: 1 m³/H = 4.4 USGPM TOTAL HEAD: 1 M = 3.28 FEET • MAX EFFICIENCY

Triple Screw Pumps

General duty screw pump in nodular cast iron.
Compact and robust design in a number variants makes it suitable for multiple applications.

K series


Triple Screw Pump - K Series	
Capacity range	Up to 174 m ³ /h / 766 gpm (at 1450 rpm)
Speed	Up to 3600 rpm
Differential pressure	Up to 16 bar / 232 psi
Viscosity range	Up to 10,000 cSt
Temperature	Up to 180°C / 356°F (300°C / 572°F magnetic coupling)
Motor	Standard and Ex motor
Pump medium	For clean, non-abrasive liquids and clean oil. Fuel, diesel, gas, and lube oil

K Series benefits


- Low maintenance costs
- High efficiency and long service life
- Low noise and vibration
- Low NPSH values



Size 5 to 118



Size 160 to 2900



Vertical Multistage Pumps

The art of transporting water is finding the right solution, with maximum efficiency, for each situation. The DPV series of vertical, multistage, centrifugal pumps is the result of 55 years of experience and the pumps can be used for numerous applications.

The new DPV pump series is revolutionary in terms of energy-savings and efficiency. Corrosion-free materials, advanced production methods and an optimised hy-

draulic assembly all contribute towards providing a unique example of craftsmanship.

The modular construction of the product enables you to modify the pump according to your specifications.



50 Hz					
Model	DPV 2	DPV 4	DPV 6	DPV 10 2P	DPV 10 4P
Capacity					
Capacity range (m ³ /h)	0.2-3.3/0.9-15	0.4-6.5/1.8-29	0.6-9/2.6-40	1.0-13.2/4-58	0.5-6.6/2-29
Nominal capacity at Qopt. (m ³ /h)/(gpm)	1.9/8.4	4/18	6.3/28	10/44	5/22
Pressure					
Norm pressure	PN16-25-40				
Maximum pump pressure (m)/(ft)	229/751	234/768	256/840	239/784	58/190
Maximum pressure at Qopt. (m)/(ft)	187/614	193/633	200/654	179/587	43/141
NPSH at Qopt. (m)/(ft)	2.2/7.2	1.2/4	1.2/4	1.2/4	0.9/3
Hydraulic assembly					
Temperature range medium	-20 - +140° C / -4 - 284° F				

50 Hz					
Model	DPV 15 2P	DPV 15 4P	DPV 25 2P	DPV 25 4P	DPV 85
Capacity					
Capacity range (m ³ /h)/(gpm)	1.8-22.5/8-99	0.98-11.3/4.3-50	2.8-35/12-154	1.4 - 17.5	8.5 - 112.8
Nominal capacity at Qopt. (m ³ /h)/(gpm)	18/79	9.8/43	28/123	14	85.7
Pressure					
Norm pressure	PN16-25-40				
Maximum pump pressure (m)/(ft)	248/814	59/194	246/807		176/577
Maximum pressure at Qopt. (m)/(ft)	193/633	44/144	185/607	45/148	132/433
NPSH at Qopt. (m)/(ft)	1.2/4	0.6/2	3.0/10	0.8/3	2.2/7
Hydraulic assembly					
Temperature range medium	-20 up to + 140° C / -4 - 284° F				

60 Hz					
Model	DPV 2	DPV 4	DPV 6	DPV 10 2P	DPV 10 4P
Capacity					
Capacity range (m ³ /h)/(gpm)	0.24-4/1-18	0.48 - 7.8	0.72 - 10.8	1.3 -15.8	0.6 - 7.9
Nominal capacity at Qopt. (m ³ /h)/(gpm)	2.3/10	4.8	7.6	13.3	6.3
Pressure					
Norm pressure	PN16-25-40				
Maximum pump pressure (m)/(gpm)	246/807	238/781	255/837	246/807	61/200
Maximum pressure at Qopt. (m)/(gpm)	201/659	195/640	199/653	173/568	44/144
NPSH at Qopt. (m)/(ft)	3/10	1.8/6	2/7	2/7	1.3/4
Hydraulic assembly					
Temperature range medium	-20 - +140° C / -4 - 284° F				

60 Hz					
Model	DPV 15 2P	DPV 15 4P	DPV 25 2P	DPV 25 4P	DPV 85
Capacity					
Capacity range (m ³ /h)/(gpm)	2.2-27/10-119	1.1-13.8/5-41	3.4-42/15-185	1.3 -15.8	10-132/44-551
Nominal capacity at Qopt. (m ³ /h)/(gpm)	21.7/96	10.9/48	34/150	34/150	100/440
Pressure					
Norm pressure	PN16-25-40				
Maximum pump pressure (m)/(ft)	233/764	57/187	210/689	87/285	151/495
Maximum pressure at Qopt. (m)/(ft)	177/551	43/141	157/515	65/213	108/354
NPSH at Qopt. (m)/(ft)	1.5/6	1.3/4	4.6/15	1.1/3.6	3.8/12
Hydraulic assembly					
Temperature range medium	-20 up to + 140° C / -4 - 284° F				

DP pump application


- ME pre-heating pump
- Hot water circulation pump
- Refrigeration water circulation pump
- HVAC water circulation pump
- Technical water pump
- Hydrophore pump
- Boiler water transfer pump
- Chemical clean pump

Low NPSH

- Extended life span as a result of favourable suction conditions
- NPSH-level 0.6 up to 3.8 (Qopt)

Modular construction

- Wide range of options
- All specials are standard
- Short delivery times



Wide range of shaft seals. Replace without dismantling the pump.

ROTAN®

Internal Gear Pumps for Marine

All the ROTAN® models have a differential pressure up to 16 bar/232 psi and a suction lift up to 0.8 bar/11.6 psi vacuum while pumping.

ROTAN® GP

ROTAN® GP – General Purpose	
Capacity range	Up to 50 m³/h / 220 gpm
Speed	Up to 1750 rpm
Differential pressure	Up to 16 bar / 232 psi
Suction lift	Up to 0.5 / 7.25 psi bar vacuum while priming Up to 0.8 bar / 11.6 psi vacuum while pumping
Viscosity range	Up to 7,500 cSt
Temperature	Up to 150°C / 302°F
Pump medium	For clean, non abrasive liquids and clean oil. Fuel, diesel, gas, and lube oil.

ROTAN® GP

General purpose pumps in cast iron. The simple and compact construction makes it a competitive pump suitable for most applications.

GP pump benefits:

- Easy installation
- Low maintenance costs
- Small footprint
- Low noise and vibration



ROTAN® GP

ROTAN® HD

ROTAN® GP – Heavy Duty	
Capacity range	Up to 250 m³/h / 1100 gpm
Speed	Up to 1750 rpm
Differential pressure	Up to 16 bar / 232 psi
Suction lift	Up to 0.5 bar / 7.25 psi vacuum while priming Up to 0.8 bar / 11.6 psi vacuum while pumping
Viscosity range	Up to 250,000 cSt
Temperature	Up to 250°C / 482°F
Pump medium	For viscous, non-corrosive liquids. Fuel, diesel, gas and lube oil.

ROTAN® HD

Heavy duty pumps in cast iron for a wide range of viscous, non-corrosive liquids. Designed for difficult applications and those involving high-viscosity oils.

HD pump benefits:

- Heavy duty
- High reliability
- Low maintenance costs
- Low noise and vibration



ROTAN® HD

ROTAN® ED

ROTAN® ED – Environmental Duty	
Capacity range	Up to 90 m³/h / 396 gpm
Speed	Up to 1750 rpm
Differential pressure	Up to 16 bar / 232 psi
Suction lift	Up to 0.5 bar / 7.25 psi vacuum while priming Up to 0.8 bar / 11.6 psi vacuum while pumping
Viscosity range	Up to 10,000 cSt
Temperature	Up to 250°C / 482°F
Pump medium	Where no leakage, liquid or gaseous, is allowed. Fuel, diesel, gas, and lube oil.

ROTAN® ED


Environmental duty - Magnetically coupled pumps in cast iron, carbon or stainless steel for ultimate protection against leakage.

ED pump benefits:

- Magnetically coupled pumps for ultimate protection against leakage
- Easy reversible direction of flow



ROTAN® ED



After-sales and service solutions

Optimization and long-term performance for your systems



Call the
DESMI Service Hotline
round the clock
at +45 96 32 81 10



The purpose of DESMI DeServe is to provide our customers with the very best service! Covering maintenance, repairs, upgrades, training, and technical support, DESMI DeServe offers services that optimize your critical flow processes.

We offer spare part kits that cover several pumps and contain the parts you need when overhauling your pumps, for example shaft seals, bearings, and O-rings. You can order individual spare parts as needed, too.

Our highly experienced and factory trained service teams provide a long list of services on your ship while

it is in port or dry dock: pre-dock inspection, installation, commissioning, on-site service, repair, maintenance, and more.

For some parts or products, we ship within 48 hours with our fast-track concept. Through our global parts database, we can also often locate the necessary part in one of our regional warehouses and ship from day to day, helping you keep operational disruptions to a minimum.



Overhaul
Videos



We exist to keep your business flowing

DESMI works closely with vessel owners, operators, and shipyards to deliver critical flow processes for diverse marine applications. Our pumps and supporting systems for marine applications, including the OptiSave™ Energy Saving System and engine room pump solutions, are trusted worldwide for dependability and the lowest total cost of ownership.

No matter which flow challenges you are facing, we can help you overcome them with class-leading equipment, solutions, and services designed specifically for your applications and environment. At DESMI, our focus has never been on discovering what we can do – it's about pushing the boundaries of what we can do for you.

Founded in Denmark in 1834, we have provided the expertise, solutions, and aftermarket support our customers need for nearly two centuries. We help you operate more efficiently and reliably, enabling your ambitions for performance, compliance, and growth whilst helping you reduce your climate impact.

Together, we can make a difference, whatever the future holds. Because we, like you, are here to make life flow. For more information, visit desmi.com

DESMI A/S

Tagholm 1
DK-9400 Nørresundby
Tel.: +45 96 32 81 11